

## RAFIX 22 QR, switching element, cage clamp terminal, silver, with coupling, for BA9s, 1 NO, 1 NO



### fields of application

- Measurement-control-regulation
- Electrical engineering
- Mechanical and system engineering
- Vehicle construction

### special features

- Switching elements with cage clamp connection
- Connection with cage clamp: Insert screwdriver (open terminal), insert cable, pull out screwdriver (terminal closes)
- Time and material savings due to elimination of ferrules for stranded wires
- Rigid wires and stranded wires can be used
- Less wiring effort by inserting the cables from the rear, as no bending of the wires is necessary.
- Disassembly by loosening the bayonet lever of the coupling



## description

RAFIX control units are modular units consisting of several parts. In the RAFIX 22 QR family, they always consist of an actuating element, coupling, and switching element, or of a light attachment, coupling, and lamp socket. For assembly, the switching elements and lamp holders are first snapped into the coupling. Then this unit is snapped onto the actuating element or the signal lamp. To release, a bayonet lever must be actuated.

For illuminable actuators and indicator lights, please use a lamp socket / LED element as the middle element in the coupling.

Switching elements marked in different colors prevent confusion in the bearing and when connecting:

- 1/2 NC contacts = 1/2 red side cover
- 1/2 normally open contacts = 1/2 green side covers
- 1 NC and 1 NO contact = 1 red and 1 green side cover
- Silver contacts = housing base color black
- Gold contacts = housing base color gray
- Lamp socket and LED element = completely black
- The connections belonging to a pair of contacts are marked in color on the connection side and provided with contact identification numbers: 1-2 = NC contact, 3-4 = NO contact
- Sicheres Schalten durch Silberkontakte (max. 400 V)
- Lieferumfang mit Kupplung

## technical data

### ➤ general

|                                                          |                                                                                                 |
|----------------------------------------------------------|-------------------------------------------------------------------------------------------------|
| Operating temperature, min.                              | -25 °C                                                                                          |
| Storage temperature, min.                                | -40 °C                                                                                          |
| Operating temperature, max.                              | 70 °C                                                                                           |
| Storage temperature, max.                                | 80 °C                                                                                           |
| illuminated                                              | Yes                                                                                             |
| Lamp socket                                              | BA9s                                                                                            |
| Packaging unit                                           | 5 pcs.                                                                                          |
| net weight                                               | 43.2 g                                                                                          |
| Operating life electrical                                | 70.000 (10A / 250V AC) cycles<br>200.000 (5A / 250V AC) cycles                                  |
| B10 electrical                                           | 90.000 (10A / 250V AC) cycles<br>210.000 (5A / 250V AC) cycles<br>515.000 (2A / 250V AC) cycles |
| Environment resistance                                   | IEC 60068-2-14<br>IEC 60068-2-30<br>IEC 60068-2-33<br>IEC 60068-2-78                            |
| Vibration-resistance according to standard IEC 60068-2-6 | 5 g at 10 - 500 Hz                                                                              |
| MOQ order                                                | 100 pcs.                                                                                        |

### direct links

- [RAFI eCatalog](#)

|                                         |                            |
|-----------------------------------------|----------------------------|
| Pollution degree acc. to DIN EN 61010-1 | Pollution degree 3         |
| RoHS compliant                          | Yes                        |
| REACH compliant                         | Yes                        |
| <b>&gt; mounting diameters</b>          |                            |
| Mounting depth                          | 56.4 mm                    |
| Outside dimension, length               | 49.9 mm                    |
| Outside dimension, width                | 39.5 mm                    |
| Outside dimension, height               | 30 mm                      |
| <b>&gt; mechanical data</b>             |                            |
| Contact function                        | 1 NO, 1 NO                 |
| Contact system                          | Bridge contact             |
| Fixing                                  | Latching                   |
| <b>&gt; electrical data</b>             |                            |
| Rated insulation voltage                | 400 V                      |
| Rated surge voltage                     | 6,000 V                    |
| Rated voltage, min.                     | 10 V                       |
| Rated voltage, max.                     | 400 V                      |
| Voltage type                            | AC / DC                    |
| Rated operating voltage                 | 10-400 V                   |
| Rated current, max.                     | 10 A                       |
| Power loss                              | 4 W                        |
| Category of use AC-15 / B300            | 400 V / 3,5 A (IEC 60947)  |
| Categories of use                       | AC-15 / B300               |
|                                         | DC-13 / Q300               |
| Category of use DC-13 / Q300            | 240 V / 0,27 A (IEC 60947) |
| Conditional short circuit current       | 1,000 A                    |

**drawings****System drawing**