

RAFIX 16, lamp socket W2 x 4.6d, quick-connect terminal, for W 2 x 4.6d



fields of application

- Measurement-control-regulation
- Electrical engineering
- Mechanical and system engineering
- Industrial robots

special features

- Lamp socket Wedge-Base W 2x4.6d for LED.
- A notch on the lamp socket indicates the cathode side.
- Mounting by snapping on or snapping into signal lamp
- Flat terminals 2.8 x 0.8 mm



description

Lamp socket for snapping in or onto signal lamps.

technical data

➤ general

Color	light gray
Operating temperature, min.	-25 °C
Storage temperature, min.	-40 °C
Operating temperature, max.	55 °C
Storage temperature, max.	85 °C
illuminated	Yes
Lamp socket	W 2 x 4.6d
Packaging unit	5 pcs.
net weight	1.8 g
Environment resistance	IEC 60068-2-14 IEC 60068-2-30 IEC 60068-2-33 IEC 60068-2-78
Shock resistance according to standard IEC 60068-2-27	50 g at 11 ms amplitude semi-sinusoidal
Vibration-resistance according to standard IEC 60068-2-6	10 g at 20 - 500 Hz
MOQ order	10 pcs.
RoHS compliant	Yes
REACH compliant	Yes

➤ mounting diameters

Mounting depth	30.5 mm
Outside dimension, length	15.9 mm
Outside dimension, width	15.9 mm

direct links

- [RAFI eCatalog](#)

Outside dimension, height 23.7 mm

> **mechanical data**

Fixing Latching

Terminal on the rear Flat quick-connect terminal 2.8 x 0.8

Solderability No

drawings

System drawing

