

CONTACTS POSITION FRONT VIEW:						
M8 - FEMALE	3 CONTACTS		4 CONTACTS		5 CONTACTS	
M12 - MALE	3 CONTACTS		4 CONTACTS		5 CONTACTS	
CONNECTIONS	PIN	WIRE	PIN	WIRE	PIN	WIRE
	1	BROWN	1	BROWN	1	BROWN
	3	BLUE	2	WHITE	2	WHITE
	4	BLACK	3	BLUE	3	BLUE
			4	BLACK	4	BLACK
					5	GREY
CODING M8 ACCORDING TO IEC 61076-2-104						
CODING M12 ACCORDING TO IEC IEC 61076-2-101						

NOTES:

1. LABEL ON THE CABLE
/ FOR CABLE Ixx PRINTING ON THE CABLE
(ENGINEERING No – THE SAME DIMENSION LIKE FOR LABEL)


2. 2 x ID CARRIER IF IN MATRIX IS "H"
OR FOR CABLE IXX & P82.

ELECTRICAL DATA:
RATED VOLTAGE: 3 contacts 60V AC/DC
4 & 5 contacts 30V AC/DC
CURRENT RATING: 3, 4, 5 contacts 3A
PROTECTION CLASS: IP67
TEMPERATURE: SEE CABLE TYPE TABLE
PACKAGING ACCORDING TO PACKAGING SPEC. 1201202000

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	
	DIMENSION UNITS	SCALE
	mm	2:1
	GENERAL TOLERANCES (UNLESS SPECIFIED)	
	ANGULAR TOL ± 1.0°	
DIVISIONAL SYMBOLS	4 PLACES	±
	3 PLACES	±
	2 PLACES	± 0.05
	1 PLACE	± 0.3
	0 PLACES	± 0.5
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION
		DRAWING
		A3-SIZE
		SERIES
		120087
		MATERIAL NUMBER
		SEE PART LIST
		CUSTOMER
		GENERAL MARKET
		SHEET NUMBER
		1 OF 3

4 8 * 0 3 0 * * * M * * * *

H = 2 PCS. OF I/D CARIERR
MOLDING/OVERMOULD:
BLANK = BLACK
BLANK = YELLOW TPE-E for cables K05
BLANK = YELLOW PUR for cables A09
A = GREY
G = BLACK
Y = YELLOW
COUPLING NUT:
BLANK=KNU/HEX
7=TEFLON
BLANK=7 for cables K05




CABLE TYPE	NO. OF WIRES	CROSS SECTION	CABLE JACKET	UL	CSA	STATIC: TEMP. / BENDING RADIUS	DYNAMIC: TEMP. / BENDING RADIUS	DRAG CHAIN	SHIELD
E02	3 4	0.25mm²	PVC BLACK	UL 2464/1729	C22.2 I/II A/B 80°C/300V	-30°C to +80°C, 10xO.D.	-10°C to +80°C, 15xO.D.	-	-
H08	3 4	0.25mm²	PUR BLACK LS0H	UL 21198/10493	C22.2 I/II A/B 80°C/300V	-40°C to +80°C, 5xO.D.	-25°C to +80°C, 10xO.D.	2 000 000 cycles at 20°C, Temp. range +5°C to +60°C	-
P02	3 4	0.25mm²	PUR / PVC BLACK	-	-	-30°C to +80°C, 7xO.D.	-5°C to +80°C, 15xO.D.	-	-
P82	3	0.34mm²	PUR IRR ORANGE	-	-	-50°C to +105°C, >5xO.D.	-40°C to +105°C, >7.5xO.D.	-	-
I02	3 4	0.25mm²	PVC CEI GREY	-	-	-30°C to +70°C	-5°C to +70°C	-	-
A09	4	0.34mm²	PVC YELLOW	UL 2661	I/II A/B 80°C/300V	-	-	-	-
K05	3 4	0.34mm²	TPE YELLOW	UL ITC or PLTC	I/II A/B 90°C/300V	max 105°C	-	-	-

OVER (mm)	UP TO AND INCLUDING (mm)	TOLERANCE (+) (mm)
0	305	+19
305	915	+45
915	1830	+56
1830	3660	+89
3660	7320	+165
7320	14640	+317
14640	30500	+610
30500	>	+2% OF LENGTH

ITEM	3P	4P	QTY.	DESCRIPTION	MATERIAL	FINISH
1	X	X	-	CABLE (SEE MATRIX)	-	-
2	X	X	-	MOULDING MATERIAL	SEE MATRIX	-
3	X	X	3/4	CONTACT 10 FE STA AU CR WRA 0.14-0.50	COPPER	Au
4	X	X	3/4	CONTACT 10 MA STA NI AU CR WRA 0.14-0.5	COPPER	Au
5	X		1,000	INSERT M8 FE 3P 0C CSE PUR BK UNSH	PUR	BK
6	X	X	1,000	GASKET OR FKM 5.0X0.8 RD 70	FKM	RD
7	X	X	1,000	NUT:M8:FEMALE-COUPLING	BRASS	
8	X		1,000	MMC-3P-MALE/MALE INSERT	PUR	BK
9	X	X	1,000	M12 MALE COUPLING NUT-BRASS;rev.1	BRASS	
10	X	X	1,000	HEAD BK M8 STR;12115-1;899921504	TPU	BK
11	X	X	1,000	HEAD BK M12 STR;12114-1;899921504	TPU	BK
12	X	X	1,000	LABEL;2.0X1.75;WRAP-B427;YE	PVC	YE
13	X	X	2,000	I/D CARRIER DIA 4-7MMX30MM	PVC	
14		X	1,000	INSERT M8 FE 4P 0C CSE PUR BK UNSH	PUR	BK
15		X	1,000	MMC-4P-MALE/MALE HOUSING	PUR	BK

DOCUMENT STATUS	P1	RELEASE DATE	2023/11/30	13:30:59
-----------------	----	--------------	------------	----------

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION													
	DIMENSION UNITS		SCALE		CURRENT REV DESC: PACKAGING SPEC ADDED				molex					
	mm		1:1											
	GENERAL TOLERANCES (UNLESS SPECIFIED)				NC/MMC-XP-FE/MM-ST/ST-XM									
ANGULAR TOL ± 1.0°														
DIVISIONAL SYMBOLS	4 PLACES		±		EC NO: 770174				PRODUCT CUSTOMER DRAWING					
	3 PLACES		±		DRWN: RSCHEIBER 2023/11/17									
	2 PLACES		± 0.05		CHK'D: RSILLER 2023/11/30									
	1 PLACE		± 0.3		APPR: RSILLER 2023/11/30									
	0 PLACES		± 0.5		INITIAL REVISION:				DOCUMENT NUMBER		DOC TYPE	DOC PART	REVISION	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				THIRD ANGLE PROJECTION		DRAWING		SERIES		MATERIAL NUMBER		CUSTOMER		SHEET NUMBER
						A3-SIZE		120087		1200878038		PSD 000		A10
										SEE PART LIST		GENERAL MARKET		2 OF 3

