

PART No. MATRIX

E 2 6 E 0 6 0 2 1 M X X X X

E=ETHERNET/
Ethernet

HEADS:
2 = M12 x Coding
6 = RJ45

HEADS STYLE:
060 = MALE STR / MALE STR

CABLE TYPE :
CABLE 21


UNITS:
M= METER
T= 10xMETER

LENGTH EXAMPLES:
005=0.5 m
010=1 m
150=15 m
T100=100 m

H= 2 PCS. OF I/D Carrier


WIRING TYPE:
E=8 Pole (STRAIGHT WIRED)

LENGTH + TOLERANCE (SEE TABLE1)




ARROW IN LINE WITH THE CODING
BRAD LOGO ON OTHER SIDE



M12 X-CODE
MALE
FRONT VIEW



M12 X-CODE
MALE



RJ45 PLUG
FRONT VIEW



BILL OF MATERIAL

ITEM	QTY	DESCRIPTION	MATERIAL	FINISH/COLOR
1	1	COUPLING NUT	BRASS	Ni PLATED
2	1	INSERT	PA	BLACK
3	8	CONTACT M12 XC MALE	BRASS	Au PLATED
4	1	SHIELDING CROSS	Zn DIE-CAST	-
5	1	SHIELDING SHELL	BRASS	Ni PLATED
6	-	OVERMOULD	TPU	BLACK
7	1	CABLE 4X(2X AWG26/7) CAT 7	TPE	GREEN TEAL SIMILAR RAL6026
8	1	PLUG RJ45	-	-
9	8	CONTACT RJ45	PHOSPHOR BRONZE	SELECTIVE Au PLATED
10	SEE PN MATRIX	ID CARRIER	PVC	TRANSPARENT
11	1	LABEL 2.0X1.75	VINYL	YELLOW

DOCUMENT STATUS P1 RELEASE DATE 2024/03/21 10:35:14

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC: CABLE COLOR UPDATED		molex			
	DIMENSION UNITS	SCALE			CSE M12 CAT6A RJ45 8P MA STR TPE XM SHLD			
$\nabla A = 0$	mm	2:1						
$\nabla E = 1$	GENERAL TOLERANCES (UNLESS SPECIFIED)							
$\nabla F = 0$	ANGULAR TOL	$\pm 1.0^\circ$						
DIVISIONAL SYMBOLS	4 PLACES	$\pm$						
	3 PLACES	$\pm$						
	2 PLACES	± 0.05						
	1 PLACE	± 0.3						
	0 PLACES	± 0.5						
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER	SHEET NUMBER
				A3-SIZE	120341	SEE TABLE 1	GENERAL MARKET	1 OF 2

