



WPET-SCG

—Self-closing Wrap



Features

- Excellent softness, easy to bend, can be loose or tight
- Good elasticity, and wear resistance
- Material: PET
- Operating temperature: -50°C~150°C
- Melting point: 250±5 °C
- Environmental standard: RoHS
- Flame retardant grade: self-extinguishing
- Standard color: black, orange

Dimensions

Spec	Inner Diameter (mm)	Maximum Bundle Diameter (mm)	Unfolded width (mm)	Package (m/roll)
WPET-SCG-003	3	4	22±2	100
WPET-SCG-005	5	6	28±2	100
WPET-SCG-008	8	9	40±2	100
WPET-SCG-010	10	11	50±5	100
WPET-SCG-013	13	14	60±5	100
WPET-SCG-016	16	17	80±5	100
WPET-SCG-019	19	20	105±5	50
WPET-SCG-025	25	27	125±8	50
WPET-SCG-029	29	31	145±8	50
WPET-SCG-038	38	40	188±10	25
WPET-SCG-050	50	52	248±10	25

Technical Data

Property	Index
Material	Polyester monofilament + polyester multifilament
Overlap (%)	≥25
Operating Temperature (°C)	-50-+150
Melting Point (°C)	240±10
Fire Resistance	N5510、NFPA130 Meet N5510, NFPA130
Wear level	ISO6722, load 7N, scratch times more than 1500 times
Approval	ROHS
Standard color	Black, orange (special colors can be customized upon request)
Cutting tool	Hot cutting