

280 Series Digital Multimeters

New



Fluke 289



Fluke 287

Advanced diagnostic and logging functionality for maximizing productivity

The new Fluke 289 and Fluke 287 represent the next generation of high-performance industrial logging multimeters, including higher accuracy and greater troubleshooting convenience than ever before. With the ability to log data and review it graphically on the large display, you can solve problems faster and help minimize downtime, while working at several locations at the same time.

- Large 50,000 count 320 x 240 (1/4 VGA) dot matrix display
- Logging function with TrendCapture for easy review of logged data


- Multiple readings per display provide more information at a glance
- "I"-info button for convenient on-board help
- PC interface for easy data transfer

In addition, the Fluke 289 provides:


- Lo Pass filter for motor drive measurements
- LoZ – Low impedance function prevents false "ghost voltage" readings
- 50 Ω range for motor winding and low ohm measurements

Features

	287	289	289/FVF
True-RMS measurements	AC, AC+DC	AC, AC+DC	AC, AC+DC
Bandwidth (voltage/current)	100 kHz / 100 kHz	100 kHz / 100 kHz	100 kHz / 100 kHz
Digital display counts (default/selectable)	50,000 / 50,000	50,000 / 50,000	50,000 / 50,000
Logging function with TrendCapture	•	•	•
Records events and trends	•	•	•
Internal memory	Up to 180 h	Up to 180 h	Up to 180 h
Saves measurements	•	•	•
Optical USB PC communications interface	•	•	•
Low input impedance function (LoZ)	•	•	•
Motor winding and low ohm measurement range	•	50 Ω	50 Ω
Low pass filter	•	•	•
Field upgradeable/expandable meter	•	•	•
Navigation keys	•	•	•
F1 – F4 soft keys/user function menus	•	•	•
I-info button/on board help screens	•	•	•
Multilingual interface	•	•	•
Saves preferred measurement setups	•	•	•
Current measurement: 20 A (30 seconds momentary; 10 A continuous)	•	•	•
Peak capture (records transients as fast as 250 μs)	•	•	•
Continuity measurement	•	•	•
Min / Max / Average with Time Stamp (records signal fluctuations)	•	•	•
IP Rating 54	•	•	•



See Minimum, Maximum & Average Values



View logged data graphically on screen



Specifications

(Check the Fluke web for detailed specifications)

Functions	Maximum	Max. resolution	287 and 289**
Voltage DC	1000 V	1 μV	±(0.25% + 5)
Voltage AC	1000 V	1 μV	±(0.4% + 40)
Current DC	10 A	0.01 μA	±(0.15% + 2)
Current AC	10 A	0.0 1μA	±(0.7% + 5)
Temperature	-200 °C to 1350 °C	0.1 °C	±(1.0% + 1°C)
Resistance	500 MΩ	0.01 Ω	±(0.05% + 2)
Conductance	50 nS	0.01 nS	±(1.0% + 10)
Capacitance	100 mF	0.001 nF	±(1.0% + 5)
Frequency	1 MHz	0.01 Hz	±(0.005% + 1)

Accuracies are best accuracies for each function.
** 287 and 289 accuracy and resolution are stated for 50,000 counts.

Battery life: 100 hours **Weight:** 1 kg
Size (HxWxD): 254 mm x 194 mm x 76.2 mm **Lifetime warranty**

Included Accessories

TL71 silicone test leads, probe holder, 6 AA batteries (installed), user manual.

The Fluke 289 / FVF kit comes with the Fluke 289 digital multimeter TL71 silicon test leads, alligator clips, 80BK thermocouple, FlukeViewForms software and cable, and a soft protective storage case.

Ordering Information

- Fluke 287 True-RMS Electronic logging multimeter with TrendCapture
- Fluke 289 True-RMS Industrial logging multimeter with TrendCapture
- Fluke 289/FVF Industrial logging multimeter and Software Combo Kit
- FVF-SC2 FlukeView Forms software including IR/USB cable

Recommended Accessories

