

FLOORS

DISSIPATIVE FLOOR COATING



It gives dissipative characteristics to a standard floor, and it is excellent in maintaining the conductive floor in operating rooms, clean rooms and data processing centres. It may also be used to maintain the table mat's dissipative surfaces.

First treatment:

- well wash the floor with the **stripper**.
- rinse with clean water.
- when dry apply two thin coats on the floor. (Yield: 1lt. for approx. 25m² per 2 coats)

Ordinary Maintenance:

- sweep the floor with a wet broom, then wash it with the **cleaner** diluted in water at 1-5% ratio.

Maintenance with spray:

- Dilute the coat in water at 30% ratio, spray it on the floor and then polish by a one-brush machine, provided with a suitable scotch-bride. (Yield: 1lt. for approx. 100m²)

Rs: < 10¹¹ Ω
7805.876

LIQUID COAT, 5 Kilos unit

Low foaming-agent detergent with highly concentrated active substances and alkalinity. It is used for cleaning and maintenance of the waxed surface.

- Biodegradable up to over 90%
- Dilution in water 1-5%
- It may be used to wash by hand and with a one-brush polisher or a washing-drying machine.



DETERGENT

7805.873

DETERGENT, 5 Kilos unit

Dewaxing alkaline detergent have to be used the first time, before applying the coating on the floor. It removes quickly multiple coats of wax and embedded dirt. It is suitable on PVC, Rubber and Hard floors.

- Biodegradable up to over 90%
- Dilution in water 5-10% machine stripping 12-16% manual stripping
- Lay off the solution and let it act for 5 minutes, then wash with water.

STRIPPER

7805.870

FLOOR STRIPPER, 5 Kilos unit

ELECSTAT-C Static Dissipative Agent

ELECSTAT-C is a non-toxic, low foaming, static dissipative agent for cleaning, used to enhance the features of the existing ESD floors or make a non-ESD floor static dissipative.

Rs: < 10¹¹ Ω

Biodegradability:

over 90%

Dilution in water:

1 to 5%

Application :

for manual or mechanical cleaning.

7805.885

Dissipative agent ELECSTAT 5kg plastic can



DISSIPATIVE FLOOR PAINT

ELECTROGUARD 30 is a two pack water based epoxy coating which can be simply applied to existing concrete floors without the need for specialist flooring contractors.

It is normally applied with two coats by brush or roller.

Electroguard 30 has an attractive satin gloss finish, easy to clean and is available in grey colour.

Number of coats : 2

Yield: approx. 8m²/litre

Rs: 10⁹ Ω - Rg: 10⁹ Ω

7805.853

ELECTROGUARD 30 medium gray, 5 litre unit
(4 litres base, 1 litre activator)

7805.856

FLOORPOX EPOXY PRIMER
for bare concrete floor

12 litre unit (6 litres base + 6 litres activator)

Number of coats : 2

approx. 16m²/litre

Yield:



FLOOR MARKING TAPE

7807.172

PVC adhesive tape, ESD Protected Area floor marking

- Self-adhesive

- 75mm wide, 33m long roll

- PVC laminated with clear PP for durability and washability