

# Pushbutton, 15.2 mm, screw connector, momentary contact function, 1 NO, bezel green



## fields of application

- Mechanical and system engineering
- Model construction
- Home technology

## special features

Drucktaster opak, nicht beleuchtbar  
 Einbaudurchmesser 15,2 mm  
 max. 250 V / 700 mA  
 1 Schließer-Kontakt, Ag  
 Schraub- oder Flachstecker-Anschluss  
 Befestigungstechnik mit Gewinding  
 Schutzart IP 40 frontseitig (IP 65 mit Schutzkappe)



## description

Pushbutton with mounting hole diameter 15.2 mm

Pushbutton with mounting hole diameter 15.2 mm, screw terminal

## technical data

### ➤ general

|                                                             |                                       |
|-------------------------------------------------------------|---------------------------------------|
| Bezel color                                                 | green                                 |
| Property of bezel / mushroom                                | opaque                                |
| Collar shape                                                | round                                 |
| Operating temperature, min.                                 | -25 °C                                |
| Storage temperature, min.                                   | -40 °C                                |
| Operating temperature, max.                                 | 85 °C                                 |
| Storage temperature, max.                                   | 90 °C                                 |
| illuminated                                                 | No                                    |
| Packaging                                                   | Box                                   |
| Packaging unit                                              | 100 pcs.                              |
| net weight                                                  | 5.0 g                                 |
| Operating life                                              | 25,000 cycles                         |
| B10                                                         | 32,500 cycles                         |
| Degree of protection, front side, according to DIN EN 60529 | IP40<br>IP65<br>IP65 with sealing cap |
| MOQ order                                                   | 100 pcs.                              |
| RoHS compliant                                              | Yes                                   |
| REACH compliant                                             | Yes                                   |

### ➤ mounting diameters

|               |         |
|---------------|---------|
| Mounting hole | 15.2 mm |
|---------------|---------|

### direct links

- [RAFI eCatalog](#)

|                          |         |
|--------------------------|---------|
| Mounting depth           | 21.5 mm |
| Installation height      | 8.2 mm  |
| Outside dimension, width | 19 mm   |

**> mechanical data**

|                        |                            |
|------------------------|----------------------------|
| Actuation function     | momentary contact function |
| Operating force, max.  | 7.5 N                      |
| Operating travel, max. | 3 mm                       |
| Contact function       | 1 NO                       |
| Contact system         | Bridge contact             |
| Contact material       | Silver                     |
| Fixing                 | Threaded ring              |
| Terminal on the rear   | Screw terminal             |

**> electrical data**

|                     |       |
|---------------------|-------|
| Rated voltage, max. | 250 V |
| Rated current, max. | 0.7 A |