

## RAFIX 22 QR, pushbutton, flat bezel, round collar, momentary contact function, front ring black, bezel red



### fields of application

- Measurement-control-regulation
- Electrical engineering
- Mechanical and system engineering
- Vehicle construction

### special features

- Opaque bezels, not illuminable
- Design adaptations through different front rings in shape and color
- Firmly molded collar seal, cannot twist or be lost during installation.
- 1-person mounting: the element is clamped by the seal in the mounting hole, and then can be screwed from behind.
- Coupling with bayonet lever as a safeguard against unintentional release of the switching element
- Robust - also suitable for operation with gloves
- Degree of protection: IP 65 at the front
- Mounting diameter 22.3 mm
- Separate switching elements required
- Close mounting of actuators (min. 30 x 50 mm) possible, as wiring is axial from behind
- Switching elements with silver contacts (max. 400 V) or gold contacts (max. 35 V / 100 mA)
- Connection types switching elements: cage clamp, screw connection or plug-in connection



description

RAFIX control units are modular units consisting of several parts. In the RAFIX 22 QR family, they always consist of an actuating element, coupling, and switching element, or of a light attachment, coupling, and lamp socket. For assembly, the switching elements and lamp holders are first snapped into the coupling. Then this unit is snapped onto the actuating element or the signal lamp. To release, a bayonet lever must be actuated.

Actuating elements (such as pushbuttons or emergency stop actuators) have the specified tactility and function only when assembled with the appropriate switching elements. For illuminated actuators and illuminated attachments, please use a lamp socket / LED element as the middle element in the coupling.

For RAFIX 22 QR actuating elements, you can choose between two collar shapes: round and square. The mounting diameter is 22.3 mm according to the standard. The anti-rotation lug can be easily removed with a screwdriver if necessary.

technical data

> general

|                                                             |                                                                      |
|-------------------------------------------------------------|----------------------------------------------------------------------|
| Bezel color                                                 | red                                                                  |
| Property of bezel / mushroom                                | opaque                                                               |
| Front ring color                                            | black                                                                |
| Collar shape                                                | round                                                                |
| Operating temperature, min.                                 | -25 °C                                                               |
| Storage temperature, min.                                   | -40 °C                                                               |
| Operating temperature, max.                                 | 70 °C                                                                |
| Storage temperature, max.                                   | 80 °C                                                                |
| illuminated                                                 | No                                                                   |
| Packaging                                                   | Box                                                                  |
| Packaging unit                                              | 10 pcs.                                                              |
| net weight                                                  | 13.7 g                                                               |
| Operating life                                              | 1,000,000 cycles                                                     |
| B10                                                         | 1,300,000 cycles                                                     |
| Degree of protection, front side, according to DIN EN 60529 | IP65                                                                 |
| Environment resistance                                      | IEC 60068-2-14<br>IEC 60068-2-30<br>IEC 60068-2-33<br>IEC 60068-2-78 |
| MOQ order                                                   | 10 pcs.                                                              |
| RoHS compliant                                              | Yes                                                                  |
| REACH compliant                                             | Yes                                                                  |

direct links

> RAFI eCatalog

> mounting diameters

|                           |            |
|---------------------------|------------|
| Mounting hole             | 22.3 mm    |
| Mounting depth            | 56.4 mm    |
| Installation height       | 9.4 mm     |
| Grid, min.                | 50 x 30 mm |
| Outside dimension, length | 29.8 mm    |
| Outside dimension, width  | 29.8 mm    |


|                           |           |
|---------------------------|-----------|
| Outside dimension, height | 32.3 mm   |
| Collar dimension          | ø 29,8 mm |

**> mechanical data**


|                            |                            |
|----------------------------|----------------------------|
| Actuation function         | momentary contact function |
| Operating force, max.      | 100 N                      |
| Operating force, min.      | 5 N                        |
| Operating travel, max.     | 4 mm                       |
| Fixing                     | Threaded ring              |
| Threaded ring torque, max. | 1.2 Nm                     |

## drawings

### Dimensioned drawing



### System drawing



## front panel drawing

