

RAFIX 22 QR, buzzer, round collar, 70 dB



fields of application

- Measurement-control-regulation
- Electrical engineering
- Mechanical and system engineering
- Vehicle construction



description

Acoustic signal transmitter matching the design of the RAFIX 22 QR actuating elements with round collar shape.

technical data

➤ general

Bezel color	slate gray
Property of bezel / mushroom	opaque
Collar shape	round
Frequency	2,400 - 3100 Hz
Operating temperature, min.	-25 °C
Storage temperature, min.	-40 °C
Operating temperature, max.	70 °C
Storage temperature, max.	80 °C
Volume 1 m	70 dB
illuminated	No
Tone type	Continuous tone
Packaging	Box
Packaging unit	2 pcs.
net weight	29.3 g
Degree of protection, front side, according to DIN EN 60529	IP65
Environment resistance	IEC 60068-2-14 IEC 60068-2-30 IEC 60068-2-33 IEC 60068-2-78
MOQ order	10 pcs.
RoHS compliant	Yes
REACH compliant	Yes

➤ mounting diameters

Mounting hole	22.3 mm
Mounting depth	56.4 mm
Installation height	9.8 mm
Grid, min.	50 x 30 mm

direct links

- [RAFI eCatalog](#)

Outside dimension, length	48.8 mm
Outside dimension, width	29.9 mm
Outside dimension, height	65.75 mm
Collar dimension	ø 29,8 mm

> mechanical data

Fixing	Threaded ring
Threaded ring torque, max.	1.2 Nm

> electrical data

Voltage type	DC
Rated operating voltage	24 V
Operating current, max.	25 mA
Power loss	0.6 W
Maximum connection cross section	1.5 mm ²
Minimum connection cross section	0.25 mm ²

drawings

front panel drawing