

Signal lamp with lamp socket, BA 9s, 18.2 mm, round bezel, 250 Volt, bezel red, Flat quick-connect terminal 6.3 x 0.8 / 2 x 2.8 x 0.8 tin-plated



fields of application

- Measurement-control-regulation
- Electrical engineering
- Mechanical and system engineering
- Signalling systems
- Model construction



description

Signal lamps for LEDs or filament/neon lamps with BA 9 s socket, mounting hole diameter 18.2 mm

technical data

➤ general

Bezel color	red
Property of bezel / mushroom	transparent
Bezel shape	round
illuminated	Yes
Lamp socket	BA9s
Packaging unit	10 pcs.
net weight	13.2 g
Degree of protection, front side, according to DIN EN 60529	IP65
MOQ order	250 pcs.
RoHS compliant	Yes
REACH compliant	Yes

direct links

- [RAFI eCatalog](#)

➤ mounting diameters

Mounting hole	18.2 mm
Mounting depth	47 mm
Installation height	14 mm
Collar dimension	22 mm

➤ mechanical data

Fixing	Threaded ring
Terminal on the rear	Flat quick-connect terminal 6.3 x 0.8 / 2 x 2.8 x 0.8 tin-plated
Solderability	Yes

➤ electrical data

Operating voltage of the luminous element, max. 250 V

drawings

Mounting hole drawing

