

EPIC® MC Module: 20pole

The mixed assembly guarantees high flexibility. For applications in machine and plant engineering, for robotics and slide-in technology.

The power module with 20 contacts is able to withstand a temperature of approximately +125 degrees for a short period and is suitable, for example, in control systems.

Info

Suitable for processing with contacts on reel
for automated production with crimping machine



Supplementary automation components from Lapp



Mechanical and plant engineering



Wind Energy

Benefits

The mix of different functions in one plug guarantees high flexibility
Assembly of individual connectors, suitable for different applications

Application range

Plant engineering
Printing machines
Control engineering

Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC002641

ETIM 5.0 Class-Description: Modular connector (industrial connector)

Classification ETIM 6:

ETIM 6.0 Class-ID: EC002641

ETIM 6.0 Class-Description: Modular connector (industrial connector)

Last Update (13.06.2023)

©2023 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

EPIC® MC Module: 20pole

	connector)
Rated voltage (V):	100 V
Rated current (A):	4 A
Pollution degree:	3
Contacts:	Copper alloy, gold-plated
Number of contacts:	20
Termination methods:	Crimp termination: 0.08 - 0.56 mm ²
Cycle of mechanical operation:	50
VDE-tested:	UL-tested:
	UL File Number: E75770
Temperature range:	-40 °C to +100 °C, short-term up to +125 °C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

EPIC® MC Module: 20pole

Article number	Article description	Contact type	Number of operating contacts	Slots	Pieces / PU
Module: 20-pin					
10383600	MCS 20 CG	male	20	1	10
10383700	MCB 20 CG	female	20	1	10