


FEMALE PLUG M12 STRAIGHT TO MALE PLUG M12 STRAIGHT



NOTES:

RATED VOLTAGE: 3, 4 contacts 250V per IEC 60664
5 contacts 60V per IEC 60664
5 contacts 250V per UL 2238
8 contacts 30V per IEC 60664

RATED CURRENT: 3, 4, 5 contacts 4A
8 contacts 2A

PROTECTION CLASS: IP 67
TEMPERATURE: -25°C / +85°C

CONTACTS POSITION FRONT VIEW:

	3 CONTACTS		4 CONTACTS		5 CONTACTS		8 CONTACTS	
FEMALE								
MALE								
CONNECTIONS	PIN	WIRE	PIN	WIRE	PIN	WIRE	PIN	WIRE
	1	BROWN	1	BROWN	1	BROWN	1	WHITE
	2	-	2	WHITE	2	WHITE	2	BROWN
	3	BLUE	3	BLUE	3	BLUE	3	GREEN
	4	BLACK	4	BLACK	4	BLACK	4	YELLOW
					5	GREY	5	GREY
							6	PINK
							7	BLUE
CODING REQUIRED TO IEC 61076-2-101								

FOR OPTIONS SEE - NUMERICAL CODE - ON SHEET 2

11	SEE SHEET 2	ID CARRIER	PVC	TRANSPARENT
10	1	LABEL YELLOW	VINYL	-
9	3 / 4 / 5 / 8	CONTACT MALE	SEE PART LIST	SELECTIVE GOLD OVER NICKEL
8	1	INSERT MALE BLACK	TPU	-
7	1	COUPLING NUT MALE	-	-
6	-	CABLE	SEE SHEET 2	-
5	-	OVERMOULDING BLACK	TPU	-
4	1	COUPLING NUT FEMALE	-	-
3	1	INSERT FEMALE BLACK	PUR	-
2	1	O-RING RED	FPM	-
1	3 / 4 / 5 / 8	CONTACT FEMALE	SEE PART LIST	SELECTIVE GOLD OVER NICKEL
ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION														
	DIMENSION UNITS		SCALE		CURRENT REV DESC: NEW P/N'S ADDED TO THE DRAWING 12335			molex							
	mm		1:1												
	GENERAL TOLERANCES (UNLESS SPECIFIED)		EC NO: 769491 DRWN: VHANDI 2023/10/30 CHK'D: RSILLER 2023/11/21 APPR: RSILLER 2023/11/21			CSE M12 XP AC FE STR MA STR XM DE									
	ANGULAR TOL ± 1.0 °														
	4 PLACES ±														
	3 PLACES ±														
	2 PLACES ± 0.05														
	DIVISIONAL SYMBOLS	1 PLACE ± 0.3		INITIAL REVISION: DRWN: JMARSZALEK 2016/09/16 APPR: RSILLER 2016/12/08			DOCUMENT NUMBER		DOC TYPE	DOC PART	REVISION				
		0 PLACES ± 0.5					1200668084		PSD	000	A17				
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION					DRAWING		SERIES		MATERIAL NUMBER		CUSTOMER	SHEET NUMBER	
		A3-SIZE					120066		SEE SHEET 3-4		GENERAL MARKET		1 OF 4		

ENGINEERING NO. - NUMERICAL CODE (Available parts see PART LIST table. Other parts available upon request).

OPTIONS

COUPLING NUTS
FEMALE MALE

8	8	X	0	3	0	X	X	X	X	X	X	X	X
---	---	---	---	---	---	---	---	---	---	---	---	---	---

88=Micro-Change
M12x1
Double ended

Contacts:
3=3 Contacts
4=4 Contacts
5=5 Contacts
8=8 Contacts

Heads style:
030=Plug Female Straight
to Plug Male Straight

Cable type: See Table







Units:
M=Meter
C=Centimeter

Length
Examples:
005=0.5 unit
010=1 unit
100=10 units

Overmold color:
Blank (Standard)=Black
A=Grey / G=Black / Y=Yellow

Coupling Nut:
Blank (Standard) & 3=Knurled Brass Ni Plated
1=Hexagonal Stainless steel _____
5=Knurled Derlin _____
7=Knurled Brass Ni Plated, Teflon Coated _____
8=Type 316 stainless steel _____
9=Knurled / Hexagonal Brass Ni Plated SW13

H= 2 pcs. of I/D Carrier PVC Transparent



CABLE INFORMATION (for more information see Cable Data Sheet).

CABLE TYPE	NO. OF WIRES	CROSS SECTION	CABLE JACKET	UL	CSA	STATIC: TEMP. / BENDING RADIUS	DYNAMIC: TEMP. / BENDING RADIUS	DRAG CHAIN	SHIELD
E02	3 / 4 / 5 / 8	0.25mm²	PVC BLACK	UL 2464/1729	C22.2 I/II A/B 80°C/300V	-30°C to +80°C, 10xO.D.	-10°C to +80°C, 15xO.D.	-	-
E03	3 / 4 / 5	0.34mm²	PVC BLACK	UL 2464/1729	C22.2 I/II A/B 80°C/300V	-30°C to +80°C, 10xO.D.	-10°C to +80°C, 15xO.D.	-	-
H08	3 / 4 / 5 / 8	0.25mm²	PUR BLACK LS0H	UL 21198/10493	C22.2 I/II A/B 80°C/300V	-40°C to +80°C, 5xO.D.	-25°C to +80°C, 10xO.D.	2 000 000 cycles at 20°C, Temp. range +5°C to +60°C	-
H09	3 / 4 / 5	0.34mm²	PUR BLACK LS0H	UL 21198/10493	C22.2 I/II A/B 80°C/300V	-40°C to +80°C, 5xO.D.	-25°C to +80°C, 10xO.D.	2 000 000 cycles at 20°C, Temp. range +5°C to +60°C	-
P02	3 / 4 / 5 / 8	0.25mm²	PUR / PVC BLACK	-	-	-30°C to +80°C, 7xO.D.	-5°C to +80°C, 15xO.D.	-	-
P03	3 / 4 / 5	0.34mm²	PUR / PVC BLACK	-	-	-30°C to +80°C, 7xO.D.	-5°C to +80°C, 15xO.D.	-	-

CABLE LENGTH TOLERANCES		
OVER [mm]	UP TO AND INCLUDING [mm]	TOLERANCES [mm]
0	305	+19
305	915	+45
915	1830	+56
1830	3660	+89
3660	7320	+165
7320	14640	+317
14640	30500	+610
30500	>	+2% OF FINISHED LENGTH

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION										
	DIMENSION UNITS		SCALE		CURRENT REV DESC: NEW P/N'S ADDED TO THE DRAWING 12335		molex				
	mm		1:1								
	GENERAL TOLERANCES (UNLESS SPECIFIED)						CSE M12 XP AC FE STR MA STR XM DE				
ANGULAR TOL ± 1.0 °											
DIVISIONAL SYMBOLS	4 PLACES		±		EC NO: 769491 DRWN: VHANDI 2023/10/30 CHK'D: RSILLER 2023/11/21 APPR: RSILLER 2023/11/21		PRODUCT CUSTOMER DRAWING				
	3 PLACES		±								
	2 PLACES		± 0.05								
	1 PLACE		± 0.3		INITIAL REVISION: DRWN: JMARSZALEK 2016/09/16 APPR: RSILLER 2016/12/08		DOCUMENT NUMBER		DOC TYPE	DOC PART	REVISION
	0 PLACES		± 0.5				1200668084		PSD	000	A17
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				THIRD ANGLE PROJECTION		DRAWING	SERIES	MATERIAL NUMBER		CUSTOMER
						A3-SIZE	120066	SEE SHEET 3-4		GENERAL MARKET	2 OF 4

DOCUMENT STATUS	P1	RELEASE DATE	2023/11/21	12:03:28
-----------------	----	--------------	------------	----------

10	9	8	7	6	5	4	3	2	1
PART LIST									
MOLEX PN			Engineering No.			Length			
1200668174			884030H09M030			3m			
1200668380			884030H09M040			4m			
1200668244			884030H09M050			5m			
1200668550			884030H09M050H			5m			
1200668737			884030H09M055			5.5m			
1200669926			884030H09M065H			6.5m			
1200669927			884030H09M070H			7m			
1200669931			884030H09M075H			7.5m			
1200669932			884030H09M080H			8m			
1200668381			884030H09M100			10m			
5P CABLE H09									
1200668509			885030H09M006			0.6m			
1200668497			885030H09M010			1m			
1200669756			885030H09M015H			1.5m			
1200668500			885030H09M020			2m			
1200669762			885030H09M020H			2m			
1200669757			885030H09M025H			2.5m			
1200668510			885030H09M030			3m			
1200669763			885030H09M030H			3m			
1200668853			885030H09M040			4m			
1200668501			885030H09M050			5m			
1200668854			885030H09M060			6m			
1200668502			885030H09M092			9.2m			
1200668511			885030H09M100			10m			
1200668683			885030H09M150			15m			
1200668684			885030H09M200			20m			
8P CABLE P02									
1200661455			888030P02M005			0.5m			
1200660579			888030P02M010			1m			
1200668803			888030P02M010H			1m			
1200660585			888030P02M100			10m			
1200668807			888030P02M100H			10m			
1200669353			888030P02M130			13m			
1200660586			888030P02M150			15m			
1200668808			888030P02M150H			15m			
1200668327			888030P02M200			20m			
1200668809			888030P02M200H			20m			