



FEMALE PLUG M12 STRAIGHT TO MALE PLUG M12 90° ANGLED






NOTES:

RATED VOLTAGE: 3, 4 contacts 250V
5 contacts 60V
8 contacts 30V
RATED CURRENT: 3, 4, 5 contacts 4A
8 contacts 2A
PROTECTION CLASS: IP67 IN MATED AND LOCKED POSITION
TEMPERATURE: -25°C / +85°C
INSULATION RESISTANCE: 10⁸ Ω MIN.
MATING CYCLES: MIN. 100



Thicker Overmold for Cables with
bigger Outer Diameter



CONTACTS POSITION FRONT VIEW:

CABLE	3 CONTACTS		4 CONTACTS		5 CONTACTS		5 CONTACTS		8 CONTACTS	
	B30, B55		B30, B33, B36, B55		B30, B33, B36, B55		B42		B41, B49	
FEMALE										
MALE										
CONNECTIONS	PIN	WIRE	PIN	WIRE	PIN	WIRE	PIN	WIRE	PIN	WIRE
	1	BROWN	1	BROWN	1	BROWN	1	BROWN	1	WHITE
	2	---	2	WHITE	2	WHITE	2	WHITE	2	BROWN
	3	BLUE	3	BLUE	3	BLUE	3	BLUE	3	GREEN
	4	BLACK	4	BLACK	4	BLACK	4	BLACK	4	YELLOW
	5	---	5	---	5	GREY	5	GREEN/ YELLOW	5	GREY
									6	PINK
									7	BLUE
									8	RED

CODING REQUIRED TO IEC 61076-2-101

DOCUMENT STATUS	P1	RELEASE DATE	2024/07/02	09:17:51
-----------------	----	--------------	------------	----------

FOR OPTIONS SEE - NUMERICAL CODE - ON SHEET 2

11	SEE PN MATRIX	I/D CARRIER	PVC	TRANSPARENT
10	1	LABEL YELLOW	VINYL	---
9	8	CONTACT M12 MALE	BRASS	SELECTIVE GOLD
	3 / 4 / 5		COPPER	OVER NICKEL
8	1	INSERT MALE BLACK	TPU	---
7	1	COUPLING NUT MALE SW13	BRASS	NICKEL
6	-	CABLE	SEE SHEET 2	---
5	-	OVERMOULDING BLACK	TPU	---
4	1	COUPLING NUT FEMALE SW13	BRASS	NICKEL
3	1	INSERT FEMALE BLACK	TPU	---
2	1	ORING RED	FPM	---
1	8	CONTACT M12 FEMALE	BRASS	SELECTIVE GOLD
	3 / 4 / 5		BRONZE	OVER NICKEL
ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION														
DIMENSION UNITS		SCALE		CURRENT REV DESC: CHANGED DIMENSIONINGSTYLE OF OVERALL LENGTH TO END TO END. UPDATED NOTES AND SORTED PART LIST USING CABLE TYPES ON SHEET 3. ADDED B41 P/N'S.				molex						
mm		1:1												
GENERAL TOLERANCES (UNLESS SPECIFIED)														
ANGULAR TOL ± 1.0 °														
4 PLACES		±		EC NO: 789428		CSE M12 XP AC FE RA WSOR MA RA XM DE								
3 PLACES		±		DRWN: AKABADI 2023/03/11										
2 PLACES		± 0.05		CHK'D: RSILLER 2024/07/02										
1 PLACE		± 0.3		APPR: RSILLER 2024/07/02		PRODUCT CUSTOMER DRAWING								
0 PLACES		± 0.5		INITIAL REVISION:		DOCUMENT NUMBER		DOC TYPE	DOC PART	REVISION				
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING		SERIES		1200668920		PSD	000	B		
													DRWN: JMARSZALEK 2016/10/17	
													2016/10/18	
													APPR: RSILLER	
				A3-SIZE		120066		SEE PART LIST		GENERAL MARKET		SHEET NUMBER		
												1 OF 3		

ENGINEERING NO. - NUMERICAL CODE (Available parts see PART LIST table. Other parts available upon request).

88X032XXXXXX

88=M12x1
Double ended

Poles:
3=3 Contacts
4=4 Contacts
5=5 Contacts
8=8 Contacts

Heads style:
032=Plug Female Straight
to Plug Male 90°

Cable type: See Table

Units:
M=Meter
C=Centimeter

Length
Examples:
005=0.5 unit
010=1 unit
100=10 unit





Overmold color:
Blank (Standard)=Black
A=Grey / G=Black / Y=Yellow / R=Red

Coupling Nut:
Blank (Standard)=Knurled/Hex Brass, Ni Plated
5=Knurled Derlin
7=Knurled Brass Ni Plated, Teflon Coated

H= 2 pcs. of I/D Carrier PVC Transparent
(Cables B36 always with 2 pcs. I/D Carrier)

COUPLING NUT

FEMALEMALE



CABLE INFORMATION (for more information see Cable Data Sheet).

CABLE TYPE	NO. OF WIRES	CROSS SECTION	CABLE JACKET	UL	CSA	STATIC: TEMP. / BENDING RADIUS	DYNAMIC: TEMP. / BENDING RADIUS	DRAG CHAIN: TEMP. / BENDING RADIUS	DRAG CHAIN	CABLE PRODUCT SPECIFICATION	CABLE SPEC. DRAWING
B30	3 / 4 / 5	0.34mm²	TPU Black	UL 21215/758	C22.2 I/II A/B 80°/600V	-40°C to +90°C >5xO.D.	-25°C to +80°C >7.5xO.D.	-5°C to +60°C >7.5xO.D.	up to 5 000 000 cycles at temp 20°C	1552200001	SD-120209-001
B33	4 / 5	0.34mm²	TPU Gray								SD-120209-001
B36	4 / 5	0.34mm²	TPU Orange								SD-120209-001
B41	8	0.25mm²	TPU Black								SD-120209-006
B42	5	0.34mm²	TPU Black								SD-120209-001
B49	8	0.25mm²	TPU Orange								SD-120209-006
B55	3 / 4 / 5	0.34mm²	TPU Yellow								n/a

CABLE LENGTH TOLERANCES

LENGTH	TOLERANCE
0m-1m	+40 mm
>1m-5m	+60 mm
>5m-10m	+80 mm
>10m-20m	+140 mm
>20m-30m	+160 mm
>30m	+1% length

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS

mm

SCALE

1:1

GENERAL TOLERANCES (UNLESS SPECIFIED)

ANGULAR TOL ± 1.0 °

4 PLACES ±

3 PLACES ±

2 PLACES ± 0.05

1 PLACE ± 0.3


0 PLACES ± 0.5

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

CURRENT REV DESC: CHANGED DIMENSIONINGSTYLE OF OVERALL LENGTH TO END TO END. UPDATED NOTES AND SORTED PART LIST USING CABLE TYPES ON SHEET 3. ADDED B41 P/N'S.

EC NO: 789428
DRWN: AKABADI 2023/03/11
CHK'D: RSILLER 2024/07/02
APPR: RSILLER 2024/07/02

INITIAL REVISION:
DRWN: JMARSZALEK 2016/10/17
APPR: RSILLER 2016/10/18

THIRD ANGLE PROJECTION


DRAWING
A3-SIZE

SERIES
120066

MATERIAL NUMBER
SEE PART LIST

CUSTOMER
GENERAL MARKET

SHEET NUMBER
2 OF 3



CSE M12 XP AC FE RA WSOR MA RA XM DE

PRODUCT CUSTOMER DRAWING

DOCUMENT NUMBER

1200668920

DOC TYPE

PSD

DOC PART

000

REVISION

B

10	9	8	7	6	5	4	3	2	1																				
PART LIST																													
MOLEX PNENGINEERING NoL [mm]			MOLEX PNENGINEERING NoL [mm]			MOLEX PNENGINEERING NoL [mm]																							
3P CABLE B30			4P CABLE B36			5P CABLE B42																							
1200668918	883032B30M006	600	1200669075	884032B36M0057Y	500	1200668930	885032B42M006	600																					
1200668919	883032B30M010	1000	1200669076	884032B36M0107Y	1000	1200668931	885032B42M010	1000																					
1200668920	883032B30M020	2000	1200669077	884032B36M0157Y	1500	1200668932	885032B42M020	2000																					
1200668921	883032B30M030	3000	1200669078	884032B36M0207Y	2000	1200668933	885032B42M030	3000																					
1200668922	883032B30M050	5000	1200669079	884032B36M0307Y	3000	1200668934	885032B42M050	5000																					
1200668923	883032B30M100	10000	1200669080	884032B36M0407Y	4000	1200668935	885032B42M100	10000																					
4P CABLE B30			1200669081			4P CABLE B55																							
1200668924	884032B30M006	600	1200669082			1200669636	884032B55M010Y	1000																					
1200668925	884032B30M010	1000	1200669083			1200669637	884032B55M020Y	2000																					
1200668926	884032B30M020	2000	1200669084			1200669638	884032B55M030Y	3000																					
1200668927	884032B30M030	3000	1200669085			1200669639	884032B55M050Y	5000																					
1200668928	884032B30M050	5000	1200669086			1200669640	884032B55M100Y	10000																					
1200668929	884032B30M100	10000	1200669087			1200669641	884032B55M150Y	15000																					
1200669634	884032B30M150	15000	1200669088			1200669642	884032B55M200Y	20000																					
1200669635	884032B30M200	20000	1200669089			5P CABLE B55																							
5P CABLE B30			5P CABLE B36			1200669695	885032B55M010Y	1000																					
1200669003	885032B30M006	600	1200669090			1200669696	885032B55M020Y	2000																					
1200669004	885032B30M010	1000	1200669091			1200669697	885032B55M030Y	3000																					
1200669005	885032B30M020	2000	1200669092			1200669698	885032B55M050Y	5000																					
1200669006	885032B30M030	3000	1200669093			1200669699	885032B55M100Y	10000																					
1200669007	885032B30M050	5000	1200669094			1200669700	885032B55M150Y	15000																					
1200669008	885032B30M100	10000	1200669095			1200669701	885032B55M200Y	20000																					
1200669693	885032B30M150	15000	1200669096																										
1200669694	885032B30M200	20000	1200669097																										
4P CABLE B33			1200669098																										
1200669889	884032B33M005A	500	1200669099																										
1200669627	884032B33M010A	1000	1200669100																										
1200669628	884032B33M020A	2000	1200669101																										
1200669629	884032B33M030A	3000	1200669102																										
1200669630	884032B33M050A	5000	1200669103																										
1200669631	884032B33M100A	10000	1200669104																										
1200669632	884032B33M150A	15000																											
1200669633	884032B33M200A	20000																											
5P CABLE B33																													
1200669912	885032B33M005A	500																											
1200669686	885032B33M010A	1000																											
1200669687	885032B33M020A	2000																											
1200669688	885032B33M030A	3000																											
1200669689	885032B33M050A	5000																											
1200669690	885032B33M100A	10000																											
1200669691	885032B33M150A	15000																											
1200669692	885032B33M200A	20000																											
1200669913	885032B33M300A	30000																											
1200669914	885032B33M400A	40000																											
1200669915	885032B33M500A	50000																											
<table><tr><td>DOCUMENT STATUS</td><td>P1</td><td>RELEASE DATE</td><td>2024/07/02</td><td>09:17:51</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>10</td><td>9</td><td>8</td><td>7</td><td>6</td><td>5</td><td>4</td><td>3</td><td>2</td><td>1</td></tr></table>										DOCUMENT STATUS	P1	RELEASE DATE	2024/07/02	09:17:51						10	9	8	7	6	5	4	3	2	1
DOCUMENT STATUS	P1	RELEASE DATE	2024/07/02	09:17:51																									
10	9	8	7	6	5	4	3	2	1																				