

10

9

8

7

6

5

4

3

2

1

PART LIST

MOLEX PN	ENGINEERING No	L+Tol. [mm]
1200698644	883S30BS1M010	1000 +40
1200698645	883S30BS1M020	2000 +60
1200698646	883S30BS1M030	3000 +60
1200698647	883S30BS1M050	5000 +60
1200698648	883S30BS1M100	10000 +80

MOLEX PN	ENGINEERING No	L+Tol. [mm]
1200698649	884S30BS1M010	1000 +40
1200698650	884S30BS1M020	2000 +60
1200699353	884S30BS1M025	2500 +60
1200698651	884S30BS1M030	3000 +60
1200698652	884S30BS1M050	5000 +60
1200698653	884S30BS1M100	10000 +80

MOLEX PN	ENGINEERING No	L+Tol. [mm]
1200699539	885S30BS1M005	500 +40
1200698654	885S30BS1M010	1000 +40
1200698757	885S30BS1M015	1500 +60
1200698655	885S30BS1M020	2000 +60
1200698656	885S30BS1M030	3000 +60
1200698758	885S30BS1M040	4000 +60
1200698657	885S30BS1M050	5000 +60
1200698658	885S30BS1M100	10000 +80
1200699482	885S30BS1M100H	10000 +80
1200699061	885S30BS1M200	20000 +140
1200699483	885S30BS1M200H	20000 +140
1200699762	885S30BS1M030H	3000 +60
1200699763	885S30BS1M150H	15000 +140
1200699764	885S30BS1M300H	30000 +160

MOLEX PN	ENGINEERING No	L+Tol. [mm]
1200698659	888S30BS2M010	1000 +40
1200698835	888S30BS2M015	1500 +60
1200698660	888S30BS2M020	2000 +60
1200698836	888S30BS2M025	2500 +60
1200698661	888S30BS2M030	3000 +60
1200698837	888S30BS2M040	4000 +60
1200698662	888S30BS2M050	5000 +60
1200698848	888S30BS2M060	6000 +80
1200699815	888S30BS2M070	7000 +80
1200698663	888S30BS2M100	10000 +80
1200698998	888S30BS2M150	15000 +140
1200699394	888S30BS2M200	20000 +140
1200699600	888S30BS2M500	50000 +500
1200699754	888S30BS2M300	30000 +160

A

CABLE SPECIFICATION

CABLE TYPE	WIRE GAUGE	CABLE JACKET	UL	CSA	static	flexing	drag chain tested	shield	other
BS1 3P,4P,5P	0.34mm ²	TPU black	STYLE 21215	yes	-40°C to +90°C 5xD	-25°C to +80°C 7.5xD	5 mio cycles	braid	WELD SLAG RESISTANCE
BS2 8P	0.25mm ²								

For Raw Cable Specification see SD-120209-003

BILL OF MATERIAL

11	2	ID CARRIER (SEE MATRIX)	PVC	-
10	1	LABEL YE	VINYL	-
9	1	INSERT XP MA M12 SH BK	PUR	-
8	X	CONTACT MA	BRASS	GOLD OVER Ni-PLATED
7	1	KNU/HEX NUT M12 MA	BRASS	Ni-PLATED
6	1	GASKET RD	FPM	-
5	1	INSERT XP FE M12 SH BK	PUR	-
4	X	CONTACT FE	BRASS	GOLD OVER Ni-PLATED
3	1	KNU/HEX NUT M12 FE	BRASS	Ni-PLATED
2	-	OVERMOULD BK	TPU	-
1	-	CABLE	SEE SHEET 2	-
ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH

DOCUMENT STATUS	P1	RELEASE DATE	2023/12/22	02:51:05
-----------------	----	--------------	------------	----------

CABLE LENGTH TOLERANCES

LENGTH	TOLERANCE
0 m - 1 m	+40 mm
>1 m - 5 m	+60 mm
>5 m - 10 m	+80 mm
>10 m - 20 m	+140 mm
>20 m - 30 m	+160 mm
>30 m	+1% length

FUNCTIONAL SYMBOLS

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

mm

1:1

GENERAL TOLERANCES (UNLESS SPECIFIED)

ANGULAR TOL ± 1.0 °

4 PLACES ±

3 PLACES ±

2 PLACES ± 0.05

1 PLACE ± 0.3

0 PLACES ± 0.5

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

THIRD ANGLE PROJECTION

DRAWING

SERIES

DOCUMENT NUMBER

1200698654

DOC TYPE

PSD

DOC PART

000

REVISION

A

INITIAL REVISION:

DRWN: RSCHIEBER 2023/12/14

APPR: RSILLER 2023/12/22

EC NO: 772068

DRWN: RSCHIEBER 2023/12/14

CHK'D: RSILLER 2023/12/22

APPR: RSILLER 2023/12/22

PRODUCT CUSTOMER DRAWING

SEE PART LIST

GENERAL MARKET

2 OF 2

</