





MATING SIDE
FEMALE CONNECTOR



MATING SIDE
MALE CONNECTOR



NOTES:

RATED VOLTAGE: MAX. 63V AC/DC
RATED CURRENT: MAX. 16A at 40°C (derating has to be considered)
IP RATING: IP67 (mated and locked condition)
TEMPERATURE RANGE: -25°C TO +85°C

CABLE PRINTING (sequence as shown below):
- MOLEX engineering no. (see page 2)
- MOLEX material no. (see page 2)
- MOLEX MAX. 63V AC/DC MAX. 16 A USL
- MOLEX AND DATE OF MANUFACTURING (YY=YEAR; WW=WEEK): MXYWW
- Not for current interrupting
- PROFINET 24V Power 4x2,5

PART ACCORDING PRODUCT SPEC: 1205010169
PACKAGING ACCORDING PACKAGING SPEC: 1201202000

TABLE 1

POS	DESCRIPTION	MATERIAL	FINISH
1	NUT M12 FE	BRASS	Ni
2	NUT M12 MA	BRASS	Ni
3	CONTACT 15 MA	BRASS	Au
4	CONTACT 15 FE	BRASS	Au
5	INSERT FEMALE	PA	BLACK
6	INSERT MALE	PA	BLACK
7	OVERMOLD	TPE	BLACK
8	CABLE 4x2.5 D10.1 WSOR	PUR	BLACK
9	GASKET OR 8.2X1 .25	FKM	BLACK
OPTIONAL 10	ID CARRIER	-	-

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION												
FUNCTIONAL SYMBOLS	DIMENSION UNITS		SCALE		CURRENT REV DESC: UPDATED ATTRIBUTE TO GENERAL MARKET IN ECTR				molex			
	mm		2:1									
 = 0	GENERAL TOLERANCES (UNLESS SPECIFIED)				CSE M12 4P LC FE STR MA RA WSOR BK XM							
 = 0	ANGULAR TOL ± 1.0 °				EC NO: 735577 DRWN: NIKHIS3 2023/01/12 CHK'D: RSILLER 2023/01/19 APPR: RSILLER 2023/01/19							
DIVISIONAL SYMBOLS	 = 0	4 PLACES		±		PRODUCT CUSTOMER DRAWING						
	3 PLACES	±										
	2 PLACES	± 0.05										
	1 PLACE	± 0.3										
	0 PLACES	± 0.5										
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING		SERIES		DOCUMENT NUMBER		DOC TYPE	DOC PART	REVISION
								1205010148		PSD	000	A1
				A2-SIZE		120501		MATERIAL NUMBER		CUSTOMER		SHEET NUMBER
								SEE TABLE 2		GENERAL MARKET		1 OF 2

ENGINEERING NO - NUMERICAL CODE (Available parts see PART LIST table. Other parts available upon request).





TABLE 2

NOMINAL SECTION 2,5mm ²			
MATERIAL NO.	ENGINEERING NO.	L [mm]	TOLERANCE [mm]
1205010148	LLP4032B65M005	500	+40
1205010149	LLP4032B65M010	1000	+40
1205010150	LLP4032B65M020	2000	+60
1205010151	LLP4032B65M030	3000	+60
1205010152	LLP4032B65M050	5000	+60
1205010153	LLP4032B65M100	10000	+80
1205010154	LLP4032B65M150	15000	+140
1205010155	LLP4032B65M200	20000	+140

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																			
	DIMENSION UNITS		SCALE		CURRENT REV DESC: UPDATED ATTRIBUTE TO GENERAL MARKET IN ECTR					molex										
	mm		1:1																	
	GENERAL TOLERANCES (UNLESS SPECIFIED)																			
	ANGULAR TOL ± 1.0°																			
	4 PLACES		±		CSE M12 4P LC FE STR MA RA WSOR BK XM															
	3 PLACES		±																	
	2 PLACES		± 0.05																	
	1 PLACE		± 0.3																	
	0 PLACES		± 0.5		PRODUCT CUSTOMER DRAWING															
DIVISIONAL SYMBOLS		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS					THIRD ANGLE PROJECTION		DRAWING		SERIES		DOCUMENT NUMBER		DOC TYPE		DOC PART		REVISION	
									A3-SIZE		120501		1205010148		PSD		000		A1	
													SEE TABLE 2		GENERAL MARKET		2 OF 2			