





MATING SIDE
FEMALE CONNECTOR



MATING SIDE
MALE CONNECTOR



NOTES:

RATED VOLTAGE: MAX. 63V AC/DC
RATED CURRENT: MAX. 12A at 40°C (derating has to be considered)
IP RATING: IP67 (mated and locked condition)
TEMPERATURE RANGE: -25°C TO +85°C

CABLE PRINTING (sequence as shown below):
- MOLEX part number
- "Made in " COUNTRY OF ORIGIN
- MOLEX AND DATE OF MANUFACTURING (YY=YEAR; WW=WEEK): MXYYYWW
- Not for current interrupting

PART ACCORDING PRODUCT SPEC: 1205010169
PACKAGING ACCORDING PACKAGING SPEC: 1201202000

TABLE 1

POS	DESCRIPTION	MATERIAL	FINISH
1	NUT M12 FE	BRASS	Ni
2	NUT M12 MA	BRASS	Ni
3	CONTACT 15 MA	BRASS	Au
4	CONTACT 15 FE	BRASS	Au
5	INSERT FEMALE	PA	GREY
6	INSERT MALE	PA	GREY
7	OVERMOLD	TPE	BLACK
8	CABLE 5x1.5 D8.6 WSOR	PUR	GREY
9	GASKET OR 8.2X1.25	FKM	BLACK
OPTIONAL 10	ID_CARRIER	-	-

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC: UPDATED ATTRIBUTE TO GENERAL MARKET IN ECTR				molex			
	DIMENSION UNITS	SCALE								
$\frac{F_A}{E} = 0$	mm	2:1	GENERAL TOLERANCES (UNLESS SPECIFIED)				CSE M12 5P LC FE STR MA RA WSOR GY XM			
$\frac{F_C}{E} = 0$										
$\frac{F_P}{E} = 0$	ANGULAR TOL	± 1.0 °	4 PLACES ±				PRODUCT CUSTOMER DRAWING			
DIVISIONAL SYMBOLS	3 PLACES ±		EC NO: 735577 DRWN: MARUTD 2023/01/11 CHK'D: RSILLER 2023/01/19 APPR: RSILLER 2023/01/19				DOCUMENT NUMBER 1205010216			
	2 PLACES ± 0.05									
	1 PLACE ± 0.3		INITIAL REVISION: DRWN: FDAFERNER 2020/08/19 APPR: RSILLER 2022/12/05				DOC TYPE PSD			
	0 PLACES ± 0.5									
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER	SHEET NUMBER		
				A2-SIZE	120501	SEE TABLE 2	GENERAL MARKET	1 OF 2		

ENGINEERING NO - NUMERICAL CODE (Available parts see PART LIST table. Other parts available upon request).




TABLE 2

NOMINAL SECTION 1,5mm²				
MATERIAL NO.	ENGINEERING NO.	L [mm]	TOLERANCE [mm]	
1205010216	LLP5032B66M005	500	+40	
1205010217	LLP5032B66M010	1000	+40	
1205010218	LLP5032B66M020	2000	+60	
1205010219	LLP5032B66M030	3000	+60	
1205010220	LLP5032B66M050	5000	+60	
1205010221	LLP5032B66M100	10000	+80	
1205010222	LLP5032B66M150	15000	+140	
1205010223	LLP5032B66M200	20000	+140	
DOCUMENT STATUS	P1	RELEASE DATE	2023/01/19	11:13:49

FUNCTIONAL SYMBOLS

FA

=

0

FE

=

0

FE

=

0

DIVISIONAL SYMBOLS

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS

SCALE

CURRENT REV DESC: UPDATED ATTRIBUTE TO GENERAL MARKET IN ECTR

mm

1:1

GENERAL TOLERANCES (UNLESS SPECIFIED)

ANGULAR TOL ± 1.0 °

4 PLACES ±

3 PLACES ±

2 PLACES ± 0.05

1 PLACE ± 0.3

0 PLACES ± 0.5

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

EC NO: 735577

DRWN: MARUTD

CHK'D: RSILLER

APPR: RSILLER

INITIAL REVISION:

DRWN: FDAFERNER

APPR: RSILLER

THIRD ANGLE PROJECTION

DRAWING

SERIES

MATERIAL NUMBER

CUSTOMER

SHEET NUMBER

2023/01/11

2023/01/19

2023/01/19

2020/08/19

2022/12/05

A3-SIZE

120501

SEE TABLE 2

GENERAL MARKET

2 OF 2

mo

lex

CSE M12 5P LC FE STR MA RA WSOR GY XM

PRODUCT CUSTOMER DRAWING

DOCUMENT NUMBER

DOC TYPE

DOC PART

REVISION

1205010216

PSD

000

A1