




MATING SIDE
FEMALE CONNECTOR



L=[mm] REFER TO TABLE 2



MATING SIDE
MALE CONNECTOR



NOTES:

RATED VOLTAGE: MAX. 63V AC/DC
RATED CURRENT: MAX. 12A at 40°C (derating has to be considered)
IP RATING: IP67 (mated and locked condition)
TEMPERATURE RANGE: -25°C TO +85°C

CABLE PRINTING (sequence as shown below):

- MOLEX part number
- "Made in " COUNTRY OF ORIGIN
- MOLEX AND DATE OF MANUFACTURING (YY=YEAR; WW=WEEK): MXYYYWW
- Not for current interrupting

PART ACCORDING PRODUCT SPEC: 1205010169
PACKAGING ACCORDING PACKAGING SPEC: 1201202000

TABLE 1

POS	DESCRIPTION	MATERIAL	FINISH
1	NUT M12 FE	BRASS	Ni
2	NUT M12 MA	BRASS	Ni
3	CONTACT 15 MA	BRASS	Au
4	CONTACT 15 FE	BRASS	Au
5	INSERT FEMALE	PA	BLACK
6	INSERT MALE	PA	BLACK
7	OVERMOLD	TPE	BLACK
8	CABLE 4x1.5 D7.9 WSOR	PUR	BLACK
9	GASKET OR 8.2X1 .25	FKM	BLACK
OPTIONAL 10	ID CARRIER	-	-

FUNCTIONAL SYMBOLS $\nabla_A = 0$ $\nabla_C = 0$ $\nabla_P = 0$ DIVISIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			molex			
	DIMENSION UNITS	SCALE	CURRENT REV DESC: UPDATED ATTRIBUTE TO GENERAL MARKET IN ECTR				
	mm	2:1					
	GENERAL TOLERANCES (UNLESS SPECIFIED)		EC NO: 735577 DRWN: MARUTD 2023/01/11 CHK'D: RSILLER 2023/01/19 APPR: RSILLER 2023/01/19 INITIAL REVISION: DRWN: FDAFERNER 2020/08/20 APPR: RSILLER 2022/12/05	CSE M12 4P LC FE STR MA RA WSOR BK XM			
	ANGULAR TOL	± 1.0 °		PRODUCT CUSTOMER DRAWING			
	4 PLACES	±		DOCUMENT NUMBER			
	3 PLACES	±		1205010248			
	2 PLACES	± 0.05		PSD 000 A1			
	1 PLACE	± 0.3		SHEET NUMBER			
	0 PLACES	± 0.5		1 OF 2			
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER
				A2-SIZE	120501	SEE TABLE 2	GENERAL MARKET

ENGINEERING NO - NUMERICAL CODE (Available parts see PART LIST table. Other parts available upon request).




TABLE 2

NOMINAL SECTION 1,5mm²					
MATERIAL NO.		ENGINEERING NO.		L [mm]	TOLERANCE [mm]
1205010248		LLP4032B43M005		500	+40
1205010249		LLP4032B43M010		1000	+40
1205010250		LLP4032B43M020		2000	+60
1205010251		LLP4032B43M030		3000	+60
1205010252		LLP4032B43M050		5000	+60
1205010253		LLP4032B43M100		10000	+80
1205010254		LLP4032B43M150		15000	+140
1205010255		LLP4032B43M200		20000	+140
DOCUMENT STATUS	P1	RELEASE DATE	2023/01/19	11:13:53	

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION														
	DIMENSION UNITS		SCALE		CURRENT REV DESC: UPDATED ATTRIBUTE TO GENERAL MARKET IN ECTR			molex							
	mm		1:1												
	GENERAL TOLERANCES (UNLESS SPECIFIED)							CSE M12 4P LC FE STR MA RA WSOR BK XM							
	ANGULAR TOL ± 1.0°														
	4 PLACES		±		EC NO: 735577 DRWN: MARUTD 2023/01/11 CHK'D: RSILLER 2023/01/19 APPR: RSILLER 2023/01/19			PRODUCT CUSTOMER DRAWING							
	3 PLACES		±												
	2 PLACES		± 0.05		INITIAL REVISION: DRWN: FDAFERNER 2020/08/20 APPR: RSILLER 2022/12/05			DOCUMENT NUMBER		DOC TYPE	DOC PART	REVISION			
	1 PLACE		± 0.3					1205010248		PSD	000	A1			
	0 PLACES		± 0.5					MATERIAL NUMBER		CUSTOMER		SHEET NUMBER			
DIVISIONAL SYMBOLS		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING		SERIES		SEE TABLE 2		GENERAL MARKET		2 OF 2	