







ITEM	DESCRIPTION
1	SCREW
2	EXTERNAL THREAD COVER
3	INSERT
4	GASKET
5	GROMMET
6	EXTERNAL THREAD NUT

C28200NOR****

SERIES _____
C28= EXTERNAL THREAD FORM A
POLES _____
2= 2 POLE & 3= 3 POLE
THREAD _____
00 = EXTERNAL THREAD
MATERIAL AND HOUSING COLOR _____
G= PA6 GRAY, N= PA6 BLACK, W= PA6 BLACK UL V0, T=TRANSPARENT
GROUND POSITION _____
0= UNMOUNTED, 2= H12, 3=H3, 6 =H6 & 9= H9
SCREW AND GASKET _____
R= INTEGRATED NBR GASKET AND IP67 SCREW
S= INTEGRATED SILICONE GASKET AND IP67 SCREW
T= PROFILE NBR GASKET AND IP67 SCREW
NON STANDARD PACKAGING _____
CN= BULK PACK UN-MOUNTED
SN= BULK PACK MOUNTED
67= NEUTRAL PACKAGING
CF= BULK PACK FULLY MOUNTED
ADDITIONAL CODES _____
SA= UL AGENCY APPROVED

- NOTES:
1. FOR SPECIFIC PART NUMBERS PLEASE CONTACT SALES OR CONSULT THE INTELLIGENT PART NUMBERS IN THE TABLE ATTACHED
 2. PRODUCT SPEC: SEE PS-121201-001
 3. PACKAGING SPEC: SEE PK-121201-001
 4. CABLE SIZES 4 - 9 mm DIAMETER
 5. TIGHTENING TORQUE: SEE PS-121201-001
 6. GROUND POSITION SHOWN H12

LAST INSPECTION NUMBER USED 8

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION													
DIMENSION UNITS		SCALE		CURRENT REV DESC: REMOVED OBSOLETE PART NUMBER AS PER PCN#512606.			molex						
mm		1:1											
GENERAL TOLERANCES (UNLESS SPECIFIED)				TYPE A ASSEMBLY SERIES 121201									
ANGULAR TOL ± °													
4 PLACES		±		EC NO: 764691 DRWN: RAVINR1 CHK'D: GGA APPR: GGA			2023/09/01 2023/10/13 2023/10/13						
3 PLACES		±											
2 PLACES		± 0.1		PRODUCT CUSTOMER DRAWING									
1 PLACE		± 0.2											
0 PLACES		±		INITIAL REVISION: DRWN: DSHEA APPR: STGRIFFIN			DOCUMENT NUMBER SD-121201-003						
										2013/09/13 2013/09/26			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING		SERIES		MATERIAL NUMBER					CUSTOMER
				A2-SIZE		121201		SEE TABLE		GENERAL MARKET		1 OF 2	

