




- ALL PARTS ARE BULK PACKED PER MOLEX PACKAGING SPECIFICATION PK-44915-003.
5. FOR USE WITH 22 TO 28 AWG SOLID OR STRANDED CONDUCTORS WITH AN INSULATION O.D. RANGE OF .037/0.94 - .072/1.07 AND A JACKET O.D. OF .217/5.5 - .256/6.5.
6. EIGHT CONDUCTOR MODULAR PLUG, CONFORMS TO F.C.C. REGULATION PART 68.5 FOR MODULAR PLUGS.
7. PLUG REQUIRES THE LOAD BAR.
8. ALL UNTOLERANCED DIMENSIONS ARE FOR REFERENCE ONLY.
9. PLUG EXCEEDS CATEGORY 5 EIA/TIA 2840, ANNEX B SPECIFICATION, PERFORMANCE TUNED TO CABLES MEETING PROPOSED CATEGORY 6 SPECIFICATIONS.
10. THE PRIMARY SHIPPING CARTON WILL BE LABELED "COMPLIANT TO ROHS DIRECTIVE 2002/95/EC AND ELV ANNEX II OF DIRECTIVE 2000/53/EC". CARTONS WITHOUT THIS LABEL MAY NOT BE COMPLIANT.
11. THIS PART CONFORMS TO CLASS B REQUIREMENTS OF COSMETIC SPECIFICATION PS 45499-002.

7. CONTRACT PART NUMBER: PS-474915-003

NOTES:
1. MATERIAL:
PLUG: POLYCARBONATE, 94V-0, COLOR: CLEAR,
LOAD BAR: POLYCARBONATE, 94V-0, COLOR: CLEAR,
CONTACTS: PHOSPHOR BRONZE.
2. CONTACT PLATING:



LOAD BAR

GENERAL TOLERANCES (UNLESS SPECIFIED)		INCH		DRAWN BY		DATE		TITLE		SCALE		DESIGN UNITS		THIRD ANGLE PROJECTION	
4 PLACES	± ---	± ---	± ---	MARGULIS	01/01/12	RJ-45 PLUG FOR PROPOSED CAT 6 SPECIFICATIONS	01/01/12		2:1	INCH	INCH	INCH	INCH	INCH	INCH
3 PLACES	± ---	± ---	± ---	CHECKED BY	01/01/12										
2 PLACES	± ---	± ---	± ---	MARGULIS	01/01/12										
1 PLACE	± ---	± ---	± ---	APPROVED BY	DATE										
ANGULAR ±1/2°				COMERCIAL		01/01/12		MOLEX		MOLEX INCORPORATED		SHEET NO.		1 OF 2	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				MATERIAL NO.		SEE CHART		DOCUMENT NO.		SD-44915-001		SHEET NO.		1 OF 2	
SIZE		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION													

MATERIAL NUMBER	4747150001
YES	4747150002
NO	
MOLEX LOGO	

