

Video/Audio cables



Applications:
Extra flex cable with separately shielded and insulated cores for assembled cables. Suitable to connect mini-Jack audio/video or Mini-DIN connectors 4-7-8 poles.

Characteristics:

Conductors: O.F.C. tinned copper
Cond. Insulation: PVC
Core colours: Yellow, Grey, Red
Shields: Spiral covering 100%
O.F.C. tinned copper
PVC
Inner Sheaths: Blue-night
Inner Sheath colours: Blue-night
External Sheath: PVC
Sheath colour: Blue-night

Conductor Resistance	Capacity Core/core	Capacity Core/shield
$\Omega/\text{Km} \pm 5\%$	pF/mt	pF/mt
210	65	230
	Max rated Voltage AC - V	Operative Temperature °C
	49	-15 / +70

Applications:
Flexible cable composed of: 3 separately shielded and insulated cores and 2 insulated cores for assembled cables. Suitable to connect 6 poles DIN 45322 plug.

Characteristics:

Conductors: O.F.C. red copper
Cond. Insulation: 3 PE
+2 PVC
Core colours: 3 Transparent
+2 Yellow, White
Shields: Spiral covering 100%
O.F.C. red copper
PVC
Inner Sheaths: Red, Blue, Yellow
Inner Sheath colours: Red, Blue, Yellow
External Sheath: PVC
Sheath colour: Black

Conductor Resistance	Capacity Core/core	Capacity Core/shield
$\Omega/\text{Km} \pm 5\%$	pF/mt	pF/mt
140		270
140		
	Max rated Voltage AC - V	Operative Temperature °C
	49	-15 / +70

tasker® Code	Cond. number	Nominal section mm²	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
TSK 1053	3	3 x 0,08 (28 AWG)	12x0,10	0,9	2,0	4,7	100	B	3,5



tasker® Code	Cond. number	Nominal section mm²	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C125	3 +2	3 x 0,12 +2 x 0,12 (26 AWG)	16x0,10	1,0	2,1	6,0	100	B	6,0

Notes: