




MG1xx-5,08-P-DI euroclamp



WIRE INSERTION
INSERIMENTO CAVO



Single module for screwless terminal block - 45° angled - with button - Modular version - Pitch 5,08mm

GENERAL INFORMATION

pitch:	5,08 mm
housing height:	14,30 mm
housing depth:	16.75 mm
dimensional class:	slow
wire section:	2.5 mm ² / 14 AWG
clamp opening size:	2.45 × 2.45 mm
wire stripping:	max 9 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	24A
voltage:	250V
test voltage:	2 kVrms/60s

MECHANICAL CHARACTERISTICS

spring releasing:	0.6 × 3.5mm
-	-

APPROVALS DATA



	-	-	UL 1059
current:	-	-	17A factory / 17A field
voltage:	-	-	300V
wire section:	-	-	12÷30AWG
torque:	-	-	-
FILE:	-	-	E178356

MATERIALS

housing:	PA - UL 94 V0
----------	---------------

AVAILABLE COLOURS



screw:
clamp/spring:
terminal:

n/a
Tin-plated copper alloy

other colours:
upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
01	MG101-5,08-P-DI	N/A	N/A	N/A