





Single-deck terminal block - Modular version - Pitch 3,5mm - 2 / 3 poles

GENERAL INFORMATION

pitch:	3,5 mm
housing height:	8,40 mm
housing depth:	6.8 mm
dimensional class:	slow
wire section:	1.0 mm ² / 16 AWG
clamp opening size:	1.8 × 1.8 mm
wire stripping:	max 6 mm
operating temperature:	-40°C ÷ +105°C

ELECTRICAL CHARACTERISTICS

current:	10A
voltage:	130V
test voltage:	1.25 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M2
recommended torque:	0.2÷0.22 Nm / 1.8÷2 in.lbs

APPROVALS DATA



current:
voltage:
FILE:

-
-
-

-
-
-

-
-
-

MATERIALS

housing:	PA - UL 94 V0
screw:	Galvanized steel
clamp/spring:	Tin-plated copper alloy
terminal:	Tin-plated copper alloy

AVAILABLE COLOURS



other colours:

upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
2	MLK132-3,5-H	N/A	N/A	N/A
3	MLK133-3,5-H	N/A	N/A	N/A
..	MLK13..-3,5-H	N/A	N/A	N/A