




Single-deck terminal block - Interlinked - Modular version - Pitch 5,08mm - 2÷3 poles

GENERAL INFORMATION

pitch:	5,08 mm
housing height:	16,00 mm
housing depth:	11 mm
dimensional class:	medium
wire section:	2.5 mm ² / 14 AWG
clamp opening size:	2.8 × 2.8 mm
wire stripping:	max 8 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	16A
voltage:	450V
test voltage:	2.5 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M3
recommended torque:	0.5÷0.55 Nm / 4.5÷4.9 in.lbs

APPROVALS DATA



current:
voltage:
FILE:

-
-
-

-
-
-

-
-
-

ADDITIONAL INFORMATION

SCIP NUMBER:

0ab5c29e-2c2a-42d2-bc27-7c61f6570969

MATERIALS

housing: PA - UL 94 V0
screw: Galvanized steel
clamp/spring: Nickeled copper alloy
terminal: Tin-plated copper alloy

AVAILABLE COLOURS



other colours: upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
2	MV252-5,08-V-B	N/A	N/A	N/A
3	MV253-5,08-V-B	N/A	N/A	N/A
..	MV25..-5,08-V-B	N/A	N/A	N/A