





Single-deck terminal block - Modular version - Pitch 7,5mm - 2÷3 poles

GENERAL INFORMATION

pitch:	7,5 mm
housing height:	13,50 mm
housing depth:	8.3 mm
dimensional class:	slow
wire section:	1.5 mm ² / 16 AWG
clamp opening size:	2.6 × 2.6 mm
wire stripping:	max 7 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	17.5A
voltage:	750V
test voltage:	3 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M2.5
recommended torque:	0.4÷0.44 Nm / 3.6÷4 in.lbs

APPROVALS DATA



EN 60998-1



EN 60998-1



UL 1059

current:	17.5A
voltage:	750V
wire section:	1.5mm ²
torque:	0.4Nm
FILE:	EP151

17.5A
750V
1.5mm ²
0.4Nm
40019705

17.5A factory / 10A field
300V
16÷30AWG
3.6Lb-in
E178356

MATERIALS

housing:	PA - UL 94 V0
----------	---------------

AVAILABLE COLOURS

screw: Galvanized steel  (STD)      
 clamp/spring: Tin-plated copper alloy other colours: upon request
 terminal: Tin-plated copper alloy

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
2	MVE172-7,5-V	N/A	N/A	N/A
3	MVE173-7,5-V	N/A	N/A	N/A
..	MVE17..-7,5-V	N/A	N/A	N/A